

WIRELESS ADAPTERS / ANTENNAS

300Mbps PCI Express

MODEL CODE	TYPE
WL7612PIN	802.11n PCI Express

FEATURES

- Complies with IEEE 802.11b/g/n standards
- 3dBi high-gain detachable antennas
- Includes EZmax setup wizard
- Supports 64/128-bit WEP, WPA, WPA2 encryptions and WPS
- Provides increased coverage, less dead spots and higher throughput (up to 300Mbps) with MIMO technology
- Supports 64/128-bit WEP, WPA (TKIP with IEEE 802.1x), WPA2 (AES with IEEE 802.1x)
- Supports Windows 2000/XP/XP64/Vista/7/8
- 2 Year Warranty



EDIMAX
NETWORKING PEOPLE TOGETHER

300Mbps Wireless PCI

MODEL CODE	TYPE
SMCWPCI-N3	802.11n 300Mbps Wireless PCI

FEATURES

- Complies with IEEE 802.11b/g/n standards
- 32-bit PCI connector
- 64-bit/128-bit/152-bit Wired Equivalent Privacy (WEP)
- Wi-Fi protected access (WPA/WPA2, WPA-PSK/WPA2-PSK)
- Advanced Encryption Standard (AES) TKIP supported
- Supports Windows 2000/XP/Vista/7/8
- 2 Year Warranty



SMC
Networks

Panel Antenna

MODEL CODE	GAIN
XI-PANEL-9	9 dBi
XI-PANEL-14	14 dBi

FEATURES

- Gain (dBi): 9 / 14
- Frequency: 2.4 - 2.5 GHz
- VSWR: <2:1
- Nominal impedance: 50 Ohms
- Connector: N female



INTELLINET
NETWORK SOLUTIONS

Omni Directional Antenna

MODEL CODE	GAIN
XI-OMNI-5	5 dBi
XI-OMNI-8	8 dBi
XI-OMNI-12	12 dBi

FEATURES

- Gain (dBi): 5 / 8 / 12
- Frequency: 2.4 - 2.5 GHz
- VSWR: <2:1
- Nominal impedance: 50 Ohms
- Connector: N female



INTELLINET
NETWORK SOLUTIONS

Omni Directional Antenna

MODEL CODE	GAIN
ANT-OMNI-2	2dBi
ANT-OMNI-5	5dBi

FEATURES

- RP-SMA type female connector
- Dual band 2.5/5.5GHz



FEATURES

- RP-SMA type female connector
- 360° horizontal, 29° vertical beam width
- Wall & magnet mounting
- Cable length 1M



SMC
Networks

LMR200 N-Type Male to RP-SMA

MODEL CODE	LENGTH
W2NMSF0	0.5M
W2NMSF1	1M
W2NMSF2	2M
W2NMSF3	3M
W2NMSF5	5M
W2NMSF7H	7.5M
W2NMSF10	10M

LMR200 N-Type Male to RP-SMA Male cable (0.63 dBi loss p/metre)



DYNAMIX