

HKSE-10



17" LCD Console Drawer

► Specifications

Specifications	HKSE-10
Panel	17" LCD Panel
Active Display Area (mm)	337.92 (H) x 270.336 (V)
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Resolution	1280 x 1024
Color Pixel Arrangement	RGB Vertical Strip
Display Mode	Normally White
Brightness (cd/m ²)	250 (Center)
Contrast Ratio	1000:1
Hot Key Control	OSD Hot Key
User Control	OSD Control (Auto Saving)
Input Signal	RGB Analog, H/V Separate
Plug-n-Play VESA	VESA DDC 2B
Power Consumption	13W (w/o Inverter, All white pattern)
Surface Treatment	Anti-Glare treatment
Approval	CE, FCC for the Product. UL, TUV, CE for Power Supply

► Features

- Modularized KVM switch design.
- Flip-open LCD panel supports resolution 1280x1024 .
- Backlight LED features less power consumption than the normal LCD monitor
- For managing computers with PS/2, USB, Mac or Sun interface.
- For rack cabinet with depth from 20" (50cm) and up (with appropriate Rear bracket & extension kit).
- Standard 19" 1U rack drawer.
- Locking mechanism locks the drawer when pulled out, pushed in, or folded down.
- Full 105 key, low-profile, sturdy keyboard included.
- A universal C-36 connector for connection between console drawer and Integra KVM switch module.
- User-replaceable keyboard with various languages support
- User-replaceable touch pad for easy replacement
- Touch pad with simulated wheel control
- Supports Sun keyboard mapping and Mac keyboard mapping.
- Ultra sturdy, tilt-free, two-piece Rear Bracket and Extension design.



	HKSE-10
Keyboard Replaceable	Yes
Touch Pad Replaceable	Yes
Module Selection	Yes
H x W x D (mm)	44 x 440 x 565