



NV-202P

VDSL2 LAN extender with PoE

The NV-202P is our low cost LAN extension solution using the G.993.2 VDSL2 standard technology and providing up to 100Mbps symmetric using only a single copper wire pair. Designed specifically for a LAN to LAN extension and supporting both symmetrical and asymmetrical transmission at up to 100/100Mbps within 300 meters and 5/1Mbps at 3000 meters, this is a perfect solution to extend LAN with PoE for IP Surveillance or PoE powered devices at any location outside of the 100 meters reach.


Features

- Cost effective bridge function to connect two PoE LANs
- Auto-detect IEEE 802.3af/at equipment
- Supports mid-span PoE mode
- Compact size and DIN rail support
- Selectable CO and CPE mode via DIP switch
- Selectable target band plan
- Selectable fast and interleaved mode
- Selectable target SNR margin 9dB or 6dB

Specifications

LAN Interface	Complies with IEEE 802.3 10Base-T 802.3u 100Base-TX, IEEE802.3af/at Connector: 2 x RJ-45 with PoE MTU: 1536 bytes	Indicators	LAN:Act/Link, PoE VDSL2: Act/Link, Line Mode: CO/CPE
VDSL2 Interface	Complies with ITU-T G993.2 Connector: RJ-11/Terminal block DMT Encoding/PTM Transmission On-board surge protection	Power	DC 48V via ACswitching adapter
4-position DIP Switch	Selectable CO or CPE mode Selectable targetband plan Selectable target SNR Margin Selectable INP and interleave mode	Power Output	30W Maximum (power injector)
Chipset	Metanoia	Dimensions	137 x 100 x 27 mm (5.39" x 3.94" x 1.06")
		Weight	About 423g
		Temperature	0~50°C (Operating), -20 ~70°C (Storage)
		Humidity	10 - 90% non-condensing
		Certification	CE, FCC, RoHS Compliant
		MTBF	50,000 hrs

Application



Ordering Information

Model Name	Description
NV-202P	VDSL2 LAN extender with PoE

sales@netsys.com.tw

*Netsys reserves the right to change specifications without prior notice



NV-202P

www.netsys.com.tw