

# WUM-001/ WUM-108D/ WUM-116D

## Digital KVM via IP Module Parts USB+PS/2 Models



## ► Specifications

		WUM-001	WUM-108D	WUM-116D
Console Port		1	1	1
Computer Port		1	8	16
Max Supported Video Mode		1600 x 1200 @ 85Hz		
Connectors		LAN RJ-45 x 1		
		Serial Supervisor (RJ-14) x 1		
		DB9 RS-232 Male (DTE) x 1		
		DC In x 1		
Computer Connectors	Integrated Keyboard + Mouse + Monitor	HDB15 Female (Grey) x 1	HDB15 Female (Grey) x 8	HDB15 Female (Grey) x 16
		Interface : USB + PS/2 Cable Type : CBM-xxxUH, CBM-xxxH		
Console Connectors	Keyboard	PS/2 x 1		
	Mouse	PS/2 x 1		
	Monitor	HDB15 (Female) x 1		
Regulatory Certifications		FCC Class A, CE, VCCI		
Power Consumption (Max.)		18 Watts		
Dimensions H x W x D (mm)		44 x 404 x 220		

## ► Features

- Embedded IPKVM module with 15"/17"/19" LCD console drawer
- RoHs compliant
- 16 bits color depth supports up to 65,536 colors
- Unique OSD feature to guide the user finish the initial setup step-by-step
- Different user accounts may have different preferences
- Firmware online upgradeable 24/7
- Custom certificate upload
- Flexible access sharing modes
- VNC screen encryption
- Internal firewall
- Supports industry-standard networking and management protocols such as TCP/IP and SNMP
- Offers secure management options including SSL encryption, SSH tunneling, and RADIUS authentication
- Platform independent: can be managed using any Java-enabled web browser
- One remote management point for multiple computers

## ▶ Connection Pattern

