

Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

APDU9953

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Plug standard	IEC 60309 32 A 2P + E
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Communication port protocol	SNMP Redfish
Provided equipment	Installation guide Rack mounting brackets Safety guide

Physical

Colour	Black
Height	182.9 cm
Width	5.6 cm
Depth	4.6 cm
Net weight	7.34 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	No

Input

Permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product certifications	VDE EAC RCM
------------------------	-------------------

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
-----------	--

Environmental

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

Relative humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Batteries & Runtime

Communication network type	10/100/1000BASE-T
----------------------------	-------------------

Packing Units

Package 1 Weight	9.95 kg
------------------	---------

Package 1 Height	204 cm
------------------	--------

Package 1 width	16.5 cm
-----------------	---------

Package 1 Length	12.4 cm
------------------	---------

Number of Units in Package 3	48
------------------------------	----

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------
