

2-PIN POWER LEAD TO BARE END

DESCRIPTION

The DYNAMIX 2-metre power lead features a standard NZ/AU 2-pin plug with a bare end (2 core, 0.75mm<sup>2</sup>), making it suitable for a wide range of general-purpose applications. Ideal for replacing damaged power cords, wiring custom electronic projects, or powering devices such as LED lighting & small appliances. Designed for flexibility & ease of installation.

FEATURES

- Insulation stripped for easy connection and installation
- 2-Pin plug
- Fine-stranded copper wire inside
- Flexible plug end
- PU outer Jacket
- Rated Current: 7.5A
- 2 core 0.75mm<sup>2</sup>



PRODUCT CODE	DESCRIPTION	LENGTH	COLOUR
C-PB2C75-2	2-Pin Plug to Bare End, 2 Core	2m	Black
C-PB2C75-2WH	2-Pin Plug to Bare End, 2 Core	2m	White

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at [contactus@dynamix.co.nz](mailto:contactus@dynamix.co.nz)  
Last updated: 7 April 2025

