

Eaton EVBAFC20A

Catalog Number: EVBAFC20A

Eaton Basic G4 Rack PDU, 0U, 22.5U, C20 input, 3m cord, 1ph, 3.7kW, 16A, 200-240V, 24 outlets (12)C13, (12)C39

General specifications



Product Name

Eaton Rack PDU G4

Catalog Number

EVBAFC20A

EAN

3553340697265

Product Length/Depth

1000 mm

Product Height

53 mm

Product Width

52 mm

Product Weight

2.5 kg

Compliances

CB
LVD Directive
RoHS Directive
WEEE Directive
Packaging Directive

Certifications

IEC 62368-1
EN IEC 63000
CE
EAC
UKCA
Cm
Ukr
cTUVus

Model Code

PDU G4 BA 0U C20 16A 1P
12xC13,12xC39

Electrical input

Input connection

C20

Wattage

3.7 kW max

Amperage Rating

16A

Input voltage

200-240V

Phase

Single-phase

Frequency rating

50/60 Hz

Cord length

3m

Electrical output

Outlets

(12) C13, (12) C39

Number of Outputs C13

12

Number of Outputs C19

12

Number of outputs (other)

12

Number of outlets with earth pin

24

Technology & communications

Type

Basic Rack PDU

Outlet control

No

Special features

Versatile C39 outlet
supports C14 or C20 power
cord plug
High retention outlets
designed to securely fit
standard power cords and
support P-Lock power cords
Color-coded outlet banks
and corresponding circuit
breakers

Ethernet interface

No

Serial interface

No

SNMP

No

Communication

No

Mass configuration

No

Additional specifications

Operating Temperature

0° to 60°C (32° to 140°F)

Accessories

Rack PDU
Rack mounting accessories
Quickstart guide
Safety Instructions

Material

Aluminium

Color

Black

Resources

Brochures

[Rack PDU G4 Brochure EN](#)

Declarations of conformity

[EU declaration of conformity Rack PDU G4](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)