



F400

Audiophile fully automatic sub-chassis turntable

Available in satin black, cherry or gloss black

High gloss:



Satin: (





- · 8,3" aluminium tonearm with cardan bearing
- E(asy)motion Wire inner tonearm cabling
- · Stiff carbon fiber headshell
- · Preadjusted Ortofon 2M Red cartridge
- 33/45/78 RPM electronic regulated DC motor
- · Vibration-damped wooden sub-chassis
- · Tonearm geometry for more balanced sound
- Damped aluminum platter with antistatic felt surface
- · Belt drive with polished flat belt
- · Viscosity-damped tonearm lift
- Automatic start/stop + automatic tonearm movement
- · Made in Germany

Speed RPM: 33, 45, 78

Wow & Flutter in % DIN / WRMS: 0.06 % / 0,035 %

Rumble: 48 dB SNR: 72 dB

MM cartridge: Ortofon 2M Red Frequency response: 20 Hz - 22 kHz Output: Phono RCA + ground cable

Dimensions (WxHxD): 430 x 130 x 365 mm

Weight: 6,3 kg

Colour: satin Black, highgloss black, cherry real wood veneer, makassar real wood veneer

Power supply: 12V DC, 150 mA

Incl. accessories: cable, dust cover, singles adapter



Der REKKORD F400

The REKKORD F400 is a fully automatic sub-chassis turntable that is not only convincing in terms of sound, but is also an eye-catcher.

The Rekkord E(asy)motion Wire inner tonearm wiring guarantees a fine sound. In conjunction with the low-friction bearing, the tonearm can overtravel with almost no resistance, which leads to a perfect music reproduction.

Thanks to well-thought-out tonearm geometry, you benefit from a brilliant and balanced sound.





Sophisticated sub-chassis design

The entire automatic system as well as the tonearm and the damped aluminum platter are built on a floating sub-chassis platform which is decoupled from the rest of the chassis. The electronic speed monitoring and control is responsible for the best possible accurate and stable speeds.

A solid wooden console made of MDF (available in satin black, high gloss black, and cherry or makassar real wood veneers) absorbs all kinds of vibrations and impact sound.

The F400 is supplied including the preadjusted Ortofon 2M Red MM cartridge.



